



RAVENOL ATF MM-PA Fluid

RAVENOL ATF MM-PA Fluid is a fully synthetic automatic transmission fluid based on PAO with special additives and inhibition what grant excellent function of the automatac gear. Due to its special formulation the properties of RAVENOL ATF MM-PA Fluid are crucial. We assure an excellent cold stability.

Application Notes

RAVENOL ATF MM-PA Fluid is a special fluid for use in automatic transmissions of Mitsubishi V5AWF.

Quality Classifications

RAVENOL ATF MM-PA Fluid is tried and tested for aggregates specifying:

Specifications

Mitsubishi V5AWF, Mitsubishi 4030401, Mitsubishi DIA QUEEN ATF-PA

Characteristic

RAVENOL ATF MM-PA Fluid offers:

- Extremely low pour point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- Neutral behaviour towards sealing materials
- Reliable protection against corrosion

Characteristics	Unit	Data	Audit
Colour		rot	visual
Density at 20°C	kg/m ³	850	EN ISO 20185
Pourpoint	°C	-53	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

10.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41