



RAVENOL Automatik-Getriebe-Oel Fluid ATF

RAVENOL Automatic Transmission Fluid ATF is a high quality transmission fluid formulated with a blend of refined base oils with special additives and inhibitors to ensure smooth and efficient operation of the transmission.

Application Notes:

RAVENOL Automatic Transmission Fluid ATF is designed for automatic fluid couplings, torque converters, servo steering systems and other hydrostatic and hydrodynamic systems for which an ATF of Type A Suffix A specification is required.

Not suitable for use where DEXRON ATF Type B, DEXRON ATF Type D or Ford specification M2C-33 E / F / G are explicitly required in the filling instructions.

Quality Classifications:

Specifications

Type A Suffix A (TASA)

Practice and tested in aggregates with filling

Allison C-4, MB 236.20, Renk Doromat, Type A Suffix A (TASA), MAN 339 Typ A, Cat. TO-4

Characteristic:

RAVENOL Automatik-Getriebe-Oel Fluid ATF offers:

- Exceptionally good resistance to aging
- A very good viscosity-temperature behavior
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Colour		rot	-
Density at 20°C	kg/m ³	884	EN ISO 12185
Viscosity at 40°C	mm ² /s	41,1	DIN 51 562
Viscosity at 100°C	mm ² /s	7,8	DIN 51 562
Viscosity index VI		167	DIN ISO 2909
Flash point (COC)	°C	182	DIN ISO 2592
Pourpoint	°C	-40	DIN ISO 3016

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.11.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41