



RAVENOL Automatik-Getriebeöl ATF 5/4 HP Fluid

RAVENOL ATF 5/4 HP Fluid is a fully synthetic ATF produced on the basis of PAO with a special additivation and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF 5/4 HP Fluid is a automatic transmission oil ATF of the latest generation for all 4- and 5 stroke automatic transmissions of ZF. It guarantees in any mode for maximum wear protection. RAVENOL ATF 5/4 HP Fluid has a neutral brown color.

Application Notes:

RAVENOL ATF 5/4 HP Fluid is suitable for use in automatic transmission of ZF Serie 4 HP (4HP20, 4HP22, 4HP24) und 5HP (5HP18, 5HP19, 5HP24, 5HP30). Maintenance-filling under normal operating conditions.

Quality Classifications:

Practice and tested in aggregates with filling

Alfa Romeo 20HP 14891900, ATF LA 2634 LT 71141, BMW 8322 9407765/9407807, Citroën/Peugeot AL4 PR 9736.22, Jaguar JLM 20237, Land Rover STC4863, Mercedes A 0019892203, Porsche 999.917.547.00, Renault DP0, VW/AUDI G 052162 A1/A2 /A6, ZF S671 090 170

Characteristic:

RAVENOL ATF 5/4 HP Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity.

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Color		braun	-
Density at 20°C	kg/m ³	847	DIN 51757
Pourpoint	°C	-42	DIN ISO 3016

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.07.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41