



RAVENOL Calibration Fluid

RAVENOL Calibration Fluid is a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Application Notes

RAVENOL Calibration Fluid V is used as a test fluid for the calibration of diesel injection pumps and as a corrosion preventive oil for the internal preservation of fuel systems.

Quality Classifications

RAVENOL Calibration Fluid is tried and tested for aggregates specifying:

Specifications

ISO 4113, SAE J 967D, MB 133.0

Characteristic

RAVENOL Calibration Fluid offers:

- Excellent wear protection
- Excellent corrosion protect
- Low tendency to foam

Characteristics	Unit	Data	Audit
Colour		farblos	visual
Density at 20°C	kg/m ³	826	EN ISO 12185
Viscosity at 40°C	mm ² /s	2,62	DIN 51 562
Flash point (COC)	°C	90	DIN ISO 2592
Pourpoint	°C	-40	DIN ISO 3016
TBN base number	mg KOH/g	2,5	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41