



RAVENOL DOT 5.1

RAVENOL DOT 5.1 is a brake fluid for the use in all vehicles with optimum ABS characteristics. There is a chemical stability and it is provided with additives which save the best lubrication efficiency.

Because of the special formulation of RAVENOL DOT 5.1 the international specifications SAE J1703, ISO 4925 and the safety regulations FMVSS 116 DOT 5.1 from the United States of America are exceeded.

Application Notes:

RAVENOL DOT 5.1 can be used in all vehicles for which the DOT 5.1 specification for brake fluids is required. It is suitable for all hydraulic brake systems with synthetic fluids.

RAVENOL DOT 5.1 is miscible with all known brake fluids of the same specification.

Quality Classifications:

Specifications

SAE J1703, ISO 4925, FMVSS 116 DOT 5.1

Characteristic:

RAVENOL DOT 5.1 offers:

- optimum ABS characteristics
- chemical stability
- best lubrication efficiency
- neutral behaviour against brake parts
- low viscosity at low temperatures
- miscible with all brake fluids of the same specification

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Boiling point	°C	min. 260	SAE J1703/1704
wet boiling point	°C	min. 180	SAE J1703/1704
Viscosity at 40°C	mm ² /s	max. 900	SAE J1703/1704

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

01.10.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41