



RAVENOL DW-1 Fluid

RAVENOL DW-1 Fluid is a fully synthetic automatic transmission fluid based on PAO with special additives and inhibition for excellent lubricating.

Due to its special formulation the properties of RAVENOL DW-1 Fluid are crucial. We assure an excellent cold stability.

Application Notes:

RAVENOL DW-1 Fluid is specially designed for use in the latest automatic transmissions of Honda.

Please note: Follow manufacturer's original equipment number!

Practice and tested in aggregates with filling

Honda 08200-9008, 08200-9009, Honda 08266-99964, 08266-99967

Characteristic:

RAVENOL DW-1 Fluid offers:

- Extremely low pour point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- Neutral behaviour towards sealing materials
- Reliable protection against corrosion

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Color		rot	-
Density at 20°C	kg/m ³	850	DIN 51 757
Pourpoint	°C	-53	DIN ISO 3016

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

10.07.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41