



RAVENOL Fork Oil Heavy 15W

RAVENOL Fork Oil Heavy 15W is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

RAVENOL Fork Oil Heavy 15W is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

Application Notes:

RAVENOL Fork Oil Heavy 15W was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

Quality Classifications:

Practice and tested in aggregates with filling

Yamaha, Kawasaki, Honda, Aprilia, BMW, Suzuki, Ducati, Triumph, Moto-Guzzi

Characteristic:

RAVENOL Fork Oil Heavy 15W offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Color		gelbbraun	-
Density at 20°C	kg/m ³	865	EN ISO 12185
Viscosity at 40°C	mm ² /s	46,0	DIN 51 562
Viscosity at 100°C	mm ² /s	8,1	DIN 51 562
VI		150	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016
TBN	mg KOH/g	0,4	DIN ISO 3771
Sulfated ash	%	ca. 0,06	-
demulsifying power		40ml/40ml/10min.	-

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.07.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41