

RAVENOL Getriebeöl CLP 220

RAVENOL Getriebeoel CLP 220 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoel CLP 220 has a low pour point and therefore a very good cold behaviour.

Application Notes

RAVENOL Getriebeoel CLP 220 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Quality Classifications

RAVENOL Getriebeoel CLP 220 is tried and tested for aggregates specifying:

Specifications

DIN 51 517 Part 3, FZG 12, US Steel 224

Characteristic

RAVENOL Getriebeoel CLP 220 offers:

- A very good, stable high-pressure impact capacity.
- · Resistant characteristics at high temperatures
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour.

Characteristics	Unit	Data	Audit	
Colour		braun	visual	
Density at 20°C	kg/m³	899	EN ISO 12185	
Viscosity at 40°C	mm²/s	217,0	DIN 51 562	
Viscosity at 220°C	mm²/s	18,5	DIN 51 562	
Viscosity index VI		94	DIN ISO 2909	
Flash point (COC)	°C	230	DIN ISO 2592	
Pourpoint	°C	-18	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.04.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0

Fax.: 052039719-40 / 41