



RAVENOL MARINE Gear Lube

RAVENOL MARINE Gear Lube contains high-quality base oils, with a balanced combination of additives. This guarantees a high load carrying capacity, wear protection and oxidation stability.

Because of the balanced additive combination good viscosity-temperature behavior, low pour point and suppression of foam formation allows use with different operating conditions.

Application Notes

RAVENOL MARINE Gear Lube is gear oil for lubricating when GL-5 transmission types are required.

Quality Classifications

Specifications

API GL-5

Practice and tested in aggregates with filling

OMC, VOLVO PENTA, Mercruiser, YANMAR

Characteristic

RAVENOL MARINE Gear Lube offers:

- Good adhesion and pressure-resistant lubricating film
- Excellent oxidation stability
- Very good viscosity-temperature behaviour
- Wear-resistant effect
- No foaming tendency
- A neutral behaviour towards metals and sealing materials

Characteristics	Unit	Data	Audit
Colour		blau	visual
Density at 15°C	kg/m ³	895	EN ISO 12185
Viscosity at 40°C	mm ² /s	140,5	DIN 51 562
Viscosity at 100°C	mm ² /s	14,1	DIN 51 562
Viscosity index VI		97	DIN ISO 2909
Flash point (COC)	°C	226	DIN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41