

RAVENOL MERCON V

RAVENOL Mercon V is an universal automatic transmission fluid ATF of the latest generation for automatic transmissions.

RAVENOL Mercon V is produced on the basis of hydrocrack oils and PAO with a special additivation and inhibition which guarantee a perfect function of the automatic transmission.

Application Notes:

RAVENOL Mercon V was especially developed for the use in Ford automatic transmissions.

RAVENOL Mercon V guarantees a maximum of corrosion protection during any operating condition.

It is recommended to flush with RAVENOL Mercon V before filling.

Quality Classifications:

Specifications

Allison C4, Mercon, GM DEXRON D III

Approvals

Ford WSS-M2C202-B, Mercon V (Lizenznummer M5060502)

Characteristic:

RAVENOL Mercon V offers:

· a very good lubricating ability even at low temperatures in winter

· a high, stable viscosity index

· a very low pour point

- · a very good oxidation stability
- · as far as possible protection against corrosion and foam formation
- · good balanced coefficient of friction
- \cdot neutral behaviour against sealing materials
- \cdot neutral behaviour because of inhibition against non ferrous metals

Attribute	Unit	Data	Audit	_
Color		rot	-	
Density at 20°C	kg/m³	0,847	EN ISO 12185	
Viscosity at -40°C	mPas(cP)	>17900	ASTM D5293	
Viscosity at 40°C	mm²/s	31,8	DIN 51 562	
Viscosity at 100°C	mm²/s	7,1	DIN 51 562	
Flash point (COC)	°C	>135	DIN ISO 2592	
Pourpoint	°C	-48	DIN ISO 3016	

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

10.07.2013 Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41