



RAVENOL MM SP-III Fluid

RAVENOL ATF MM SP-III Fluid is universal ATF (Automatic Transmission Fluid).

RAVENOL ATF MM SP-III Fluid is based on hydro cracking oils and PAO with special additives and inhibition to ensure the proper operation of the automatic transmission.

Application Notes:

RAVENOL ATF MM SP-III Fluid was developed for use in automatic transmission, especially for Mitsubishi, Hyundai and KIA.

RAVENOL ATF MM SP-III Fluid guarantees maximum wear protection in all operating conditions.

RAVENOL ATF MM SP-III Fluid can replace SP und SP-II Fluids.

It is advisable to flush with RAVENOL ATF MM SP-III Fluid before filling with RAVENOL ATF MM SP-III Fluid.

Quality Classifications:

Practice and tested in aggregates with filling

Automatik-Getriebe v. Mitsubishi/Hyundai/KIA

Characteristic:

RAVENOL ATF MM SP-III Fluid offers:

- Very good lubricating properties also at low temperatures in winter
- High, stable viscosity index
- Very low pour point
- Excellent oxidation stability
- Protection against wear, corrosion and foaming
- Good concerted friction characteristic
- Neutral behavior towards sealing materials
- Neutral behavior by inhibition to non-ferrous metals

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Color		rot	-
Density at 20°C	kg/m ³	847	EN ISO 12185
Pourpoint	°C	-48	DIN ISO 3016

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.07.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41