



RAVENOL Motogear SAE 80W-90 GL-5

RAVENOL Motogear SAE 80W-90 GL-5 is a mineral-based motorcycle gearbox oil formulated to ensure optimum gear lubrication in all conditions. Designed to offer a stable oil film to reduce friction and prevent wear and corrosion.

Application Notes

RAVENOL Motogear SAE 80W-90 GL-5 is suitable for use in all manual transmissions of both 2 - and 4-stroke motorcycles where an oil of SAE 80W-90 API GL-5 is required.

Quality Classifications

Specifications

API GL-5

Characteristic

RAVENOL Motogear SAE 80W-90 GL-5 offers:

- A high-pressure stable lubricating film
- Reduced gear noise and excellent power transmission characteristics
- Very good oxidation stability
- Enhanced detergent and dispersant characteristics
- Very low foaming properties
- Extremely good resistance to aging
- Very good viscosity-temperature behavior
- Exceptional wear protection
- Extremely good corrosion resistance, does not attack ferrous metals
- Compatible with all types of sealing materials

Characteristics	Unit	Data	Audit
Colour		brown	visual
Density at 15°C	kg/m ³	895	EN ISO 12185
Viscosity at 40°C	mm ² /s	140, 5	DIN 51 562
Viscosity at 100°C	mm ² /s	14,1	DIN 51 562
Viscosity index VI		97	DIN ISO 2909
Flash point (COC)	°C	226	DIN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

04.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41