



## RAVENOL QUAD 4T SAE 10W-40

RAVENOL QUAD 4T SAE 10W-40 4-stroke motor oil is especially developed for quads and ATVs (all-terrain vehicles). It is used in 4-stroke quad engines from KAWASAKI, YAMAHA, BOMBARDIER and SUZUKI. Special EP additives reliably protect the transmission system against wear and facilitate start-up when in gear as well as the process of changing gears. The smooth-running viscosity of RAVENOL QUAD 4T SAE 10W-40 allows for a low-wear cold start even in extremely low outdoor temperatures.

Even in low gears and under extremely high loads RAVENOL QUAD 4T SAE 10W-40 ensures a strong lubricant film and protects against wear. Special EP additives reliably protect the transmission system against wear, facilitate start-up when in gear as well as the process of changing gears. Compatible with wet clutch system and catalytic converters.

Can be used all year round. Low tendency to evaporation and therefore, low oil consumption.

### Application Notes

RAVENOL QUAD 4T SAE 10W-40 is used for 4-stroke quad engines from leading manufacturers. Compatible with wet clutch system and catalytic converters.

RAVENOL QUAD 4T SAE 10W-40 is an all season motor oil.

### Approvals

Erfüllt: JASO MA2 T903:2011, Freigabe JASO 049RAV160, License: API SL

### Practice and tested in aggregates with filling

4-stroke quad engines from KAWASAKI, YAMAHA, BOMBARDIER, SUZUKI, HONDA

### Characteristic

RAVENOL QUAD 4T SAE 10W-40 offers:

- Low-wear cold start even at extremely low outdoor temperatures
- A strong lubricant film and high wear protection
- Compatibility with wet clutch systems and catalytic converters
- All season application
- High corrosion and wear protection
- Low tendency to evaporation and therefore, low oil consumption

Characteristics	Unit	Data	Audit
Colour		grün	visual
Density at 20°C	kg/m <sup>3</sup>	870	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	91,3	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	14,0	DIN 51 562
Viscosity index VI		157	DIN ISO 2909
Flash point (COC)	°C	210	DIN ISO 2592
Pourpoint	°C	-35	DIN ISO 3016
TBN	mg KOH/g	7,0	DIN ISO 3771
Sulphated ash	%wt.	1,5	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41