



RAVENOL RFS SAE 15W-50

RAVENOL RFS Racing Formel Sport 15W-50 is a semi-synthetic multigrade engine oil based on esters and poly-alpha olefins. Suitable for use in modern gasoline engines at car race even under difficult conditions. Due to its high viscosity index, it's good shear stability and a highly effective special additives RAVENOL RFS Racing Formel Sport 15W-50 formula is also suitable for extremely sporty driving style. Increased protection against wear, corrosion (oxidation) and foaming.

Application Notes:

RAVENOL RFS Racing Formel Sport 15W-50 is used as a special oil for car racing such as DMV Tourenwagen Challenge even under difficult conditions.

Quality Classifications:

Specifications

API SL/CF, ACEA A3/B3

Characteristic:

RAVENOL RFS Racing Formel Sport 15W-50 offers:

- The prevention of sludge formation
- A very high viscosity index
- A very good cold start characteristics
- Low friction loss therefore little wear too
- Natural oxidation stability
- Very low evaporation

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Density at 20°C	kg/m ³	873	EN ISO 12185
Viscosity at -20°C	mPa.s	6800	ASTM D5293
Viscosity at 40°C	mm ² /s	131,0	DIN 51 562
Viscosity at 100°C	mm ² /s	17,1	DIN 51 562
VI		143	DIN ISO 2909
Flash point (COC)	°C	226	DIN ISO 2592
Pourpoint	°C	- 27	DIN ISO 3016
TBN	mg KOH/g	6,7	DIN ISO 3771
Sulfated ash	%	0,89	-

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.07.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41