



RAVENOL STOU SAE 20W-40

RAVENOL STOU SAE 20W-40 is a multi-purpose super tractor oil universal for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers listed below, and can be used in engines, transmissions and hydraulic systems of most tractors in all seasons which require this grade of oil.

Application Notes

RAVENOL STOU SAE 20W-40 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes) and as a hydraulic oil where this specification of product is required.

Quality Classifications

Specifications

API CG-4, ACEA E2, API GL-4

Practice and tested in aggregates with filling

Ford M2C-159C, MF M-1143/1144, MB 227.1, ZF TE-ML 06B, ZF TE-ML 07B, Allison C4, Caterpillar TO-2, Ford M2C-86A, Ford M2C-134D, John Deere J 27, NH 420A, NH 410B

Characteristic

RAVENOL STOU SAE 20W-40 offers:

- A high dispersion and detergent capability
- Exceptional protection against wear, corrosion and foaming
- High oxidation stability
- Excellent extreme pressure properties
- A high and stable viscosity index

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 15°C	kg/m ³	896	EN ISO 12185
Viscosity at 40°C	mm ² /s	115,0	DIN 51 562
Viscosity at 100°C	mm ² /s	13,0	DIN 51 562
Viscosity index VI		107	DIN ISO 2909
Flash point (COC)	°C	234	DIN ISO 2592
Pourpoint	°C	-29	DIN ISO 3016
TBN	mg KOH/g	10,9	DIN ISO 3771
Sulphated ash	%wt.	1,45	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

12.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41