



RAVENOL Super Truck SAE 40

RAVENOL Super Truck SAE 40 is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

RAVENOL Super Truck SAE 40 is a top-quality product with high safety reserves.

Application Notes

RAVENOL Super Truck SAE 40 is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Quality Classifications

Specifications

API CF-4, ACEA E2/B4

Practice and tested in aggregates with filling

MTU Type 1, Voith DIWA, MAN 270, MB 228.0, ZF TE-ML 04B

Characteristic

RAVENOL Super Truck SAE 40 offers:

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysis
- Reduced emissions

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Colour | | gelbbraun | visual |
| Density at 20°C | kg/m ³ | 887 | EN ISO 12185 |
| Viscosity at 40°C | mm ² /s | 131 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 13,9 | DIN 51 562 |
| Viscosity index VI | | 103 | DIN ISO 2909 |
| Flash point (COC) | °C | 232 | DIN ISO 2592 |
| Pourpoint | °C | -21 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41