



RAVENOL RHP SAE 75W-90



ART.-NR. 1145100

1 L | 1145100-001
4 L | 1145100-004
20 L | 1145100-020
20 L | 1145100-B20
60 L | 1145100-060
60 L | 1145100-D60
1000 L | 1145100-700

FABRICATION FULLY SYNTHETIC

RAVENOL RHP Racing High Performance Gear SAE 75W-90 is a modern, PAO (poly-alpha-olefin) based fully synthetic racing gear oil with USVO® Technology.

RAVENOL RHP Racing High Performance Gear SAE 75W-90 was developed as manual and differential oil for use in racing vehicles.

RAVENOL RHP Racing High Performance Gear SAE 75W-90 is particularly recommended for use in manual transmissions and rear axle with integrated locking differential.

The USVO® technology offers high performance, improved gear protection and optimized gear cleanliness for your vehicle.

Special additives guarantee limited slip properties, a high load carrying capacity, stable viscosity, optimum wear protection, low foaming, proper lubrication and reducing the heating of the transmission.

RAVENOL RHP Racing High Performance Gear SAE 75W-90 offers excellent anti-wear properties and an optimum viscosity-temperature behavior.

Application Notes

RAVENOL RHP Racing High Performance Gear SAE 75W-90 is a fully synthetic racing gear oil for use in racing cars and is particularly recommended for use in manual transmissions and rear axle with integrated locking differential.

Characteristics

RAVENOL RHP Racing High Performance Gear SAE 75W-90 offers:

- A stable high-pressure lubricating oil film even at high temperatures and under high stress.
- Excellent shear stability and excellent thermal stability.
- A very good viscosity-temperature behaviour.
- An excellent aging resistance and high oxidation resistance.
- A very good wear protection, excellent EP characteristics.
- A low foaming even at high speeds.
- Good compatibility with non-ferrous metals and sealing materials.
- Good circuit behaviour at low temperatures, low pour Point.
- Reduced noise transmission through low vibration even in hot oil through the oil film with good adhesion.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	868,0	EN ISO 12185
Colour		gelb	visual
Viscosity at 100°C	mm ² /s	16,1	DIN 51562-10
Viscosity at 40°C	mm ² /s	92,6	DIN 51562-10
Viscosity index VI		188	DIN ISO 2909
Brookfield Viscosity	mPa*s	33.800	ASTM D2983
Pourpoint	°C	-57	DIN ISO 3016
Flash point	°C	200	DIN ISO 2592
Foaming behavior	ml/ml	0/0, 10/0, 0/0	ASTM D892
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 30. October 2019