



RAVENOL ATF 6HP Fluid

RAVENOL ATF 6HP Fluid is automatic transmission oil ATF, produced on the basis of hydrocrack oils and PAO with special additives and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF 6HP Fluid is one of the ATF (Automatic Transmission Fluid) of the newly developed generation for all 6-motion automatic transmission of ZF. A maximum of wear protection in every operating state is guaranteed. RAVENOL ATF 6 HP Fluid has a neutrally brown colour.

Application Notes:

RAVENOL ATF 6 HP Fluid was developed for use in the newly developed 6HP-series transmission of ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34, also for 5-motion automatic transmission 5HP-series. It is backwardly compatible for all earlier versions of ZF 4 and 5 gear passenger car automatic transmission with the exception of 6 HP26A61 in vehicles with AUDI W12 (only original VW G055162A2 blue) and 6HP19X for AUDI Q7, 6HP19A, 6HP28AF (only original VW G060162A2 green).

Quality Classifications:

RAVENOL ATF 6 HP Fluid is tried and tested for aggregates specifying:

Specifications

BMW 83220144137 ATF M1375.4 83220142516, 83222305396 (ATF2), FORD Mercon SP XT-6-QSP (6R60, 6R75, 6R80), Jaguar C2C 8432, Land Rover TYK 500050, VW/AUDI G 055005 A1/A2/A6, ZF S671 090 252/3/5

Characteristic:

RAVENOL ATF 6 HP Fluid offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very low pour point
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- a neutral behaviour against sealing materials
- a high thermal and oxidative stability
- a excellent cooling capacity
- a excellent shear stability
- lowest evaporation losses
- a neutral behaviour because of inhibition against non ferrous metals

<u>Attribute</u>	<u>Unit</u>	<u>Data</u>	<u>Audit</u>
Colour		braun	visual
Density at 20°C	kg/m ³	847	EN ISO 12185
Pourpoint	°C	-42	DIN ISO 3016

All data are approximate and subject to customary variations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

07.11.2013

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41