

# **RAVENOL ATF Dexron II E**

RAVENOL ATF Dexron II E is high performance fully synthetic automatic transmission oil ATF for use in torque converter transmission and power shift transmission of vehicles with specification GM Dexron II E, Ford Mercon and Allison C-4.

## **Application Notes**

RAVENOL ATF Dexron II E is developed for use in automatic transmission and torque converter transmission and power shift transmission with required specification.

RAVENOL ATF Dexron II E is recommended if ATF Type Dexron II E is to be used according to manufacturer's specification.

## **Quality Classifications**

RAVENOL ATF Dexron II E is approved and corresponds to:

#### Specifications

GM Dexron II E, Ford Mercon

#### Approvals

Voith 55.6336.3x Extended Drain (G1363), MB 236.8, Allison C4-32652009 (ATF II E)

#### Practice and tested in aggregates with filling

MB 236.5, MAN 339 Typ Z-2, MAN 339 Typ V-2, ZF TE-ML 04D, 09X, 14B, 16L, Cat. TO-2  $\,$ 

## Characteristic

RAVENOL ATF Dexron II E offers:

- reliable protection against wear, sludge, adhesion and corrosion
- a very shear stable viscosity-temperature behavior
- can be used both at very low and very high temperatures
- an extremely high thermal load
- no foaming, even under the heaviest loads
- compatibility with sealing materials

Characteristics	Unit	Data	Audit	
Colour		rot	visual	
Density at 20°C	kg/m³	832	EN ISO 12185	
Viscosity at 40°C	mm²/s	32	DIN 51 562	
Viscosity at 100°C	mm²/s	7,5	DIN 51 562	
Flash point (COC)	°C	203	DIN ISO 2592	
Pourpoint	°C	-51	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

## 14.04.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41