



RAVENOL Getriebeöl EPX SAE 85W-90 GL 5

In order to avoid the seasonal change of the transmission oil RAVENOL Getriebeöl EPX SAE 85W-90 GL 5 was developed. It can be used in winter as well as in summer. Its universal use reduces the risk of mix-up and storage. Because of the balanced additive combination characteristics like a high pressure absorption capacity, a superior viscosity temperature behaviour, a high oxidation stability, low pour points, a good corrosion protection and non-sludging are guaranteed.

Application Notes

RAVENOL Getriebeöl EPX SAE 85W-90 GL 5 is compatible with all brand-name transmission oils. In case of changing to RAVENOL Getriebeöl EPX SAE 85W-90 GL 5 flushing is not necessary.

RAVENOL Getriebeöl EPX SAE 85W-90 GL 5 can be used in manual transmissions, axle drives, distributor and intermediate transmissions in vehicles and working machines.

Specifications

API GL-5, MIL-L-2105 D

Practice and tested in aggregates with filling

ZF TE-ML 05A, ZF TE-ML 16B, ZF TE-ML 17B, ZF TE-ML 19B, MAN 342 Typ M1, MB 235.0, Ford SQM-2C-9002AA

Characteristic

RAVENOL Getriebeöl EPX SAE 85W-90 GL 5 offers:

- An optimum cold flow capacity
- An excellent corrosion protection also regarding short distances in winter
- Extreme pressure stability, therefore an excellent corrosion protection at all loads, reduced transmission noises and a best transmission efficiency under full power that means also in case of very hot oil
- An excellent shear stability
- A very good oxidation stability, no foam
- No oil thickening power respectively deposits
- An extremely high aging resistant
- A very good viscosity temperature behaviour
- An efficient corrosion protection
- Protection against corrosion, sludge and sticking
- An excellent corrosion protection, no rust, no attack of nonferrous metals
- Neutral behaviour of sealing materials that means the transmissions stay closed, no oil loss

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	895	DIN 51757
Viscosity at 40°C	mm ² /s	142,6	DIN 51 562
Viscosity at 100°C	mm ² /s	14,2	DIN 51 562
Viscosity index VI		97	DIN ISO 2909
Flash point (COC)	°C	226	DIN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41