



RAVENOL Getriebeoel TSG SAE 75W-90



VISCOSITY 75W-90

SPECIFICATIONS API GL-4

FABRICATION SEMI-SYNTHETIC

RECOMMENDATIONS VW 501 50 | FORD M2C-175 | GM OPEL B 040 104 3
| VW G052 911 A2

ART.-NR. 1222101

1 L	1222101-001
4 L	1222101-004
10 L	1222101-010
20 L	1222101-020
20 L	1222101-B20
60 L	1222101-060
60 L	1222101-D60
208 L	1222101-208
208 L	1222101-D28
1000 L	1222101-700

RAVENOL Getriebeoel TSG SAE 75W-90 is a semi-synthetic multi-purpose transmission oil for maximum duty manual transmissions.

RAVENOL Getriebeoel TSG SAE 75W-90 is designed based on high-quality synthetic base oils with special additive treatment and inhibition coordinated to the increased stress on manual transmission oils and ensuring trouble-free transmission function.

Application Notes

RAVENOL Getriebeoel TSG SAE 75W-90 is suitable for highly stressed manual transmissions (with and without synchronising), transfer cases and steering gearboxes in vehicles and work machines.

Characteristics

RAVENOL Getriebeoel TSG SAE 75W-90 offers:

- excellent ageing resistance
- extra high pressure absorption properties
- optimal viscosity-temperature properties
- excellent low temperature properties
- shearing stability
- stable lubricating film even under high stress
- extremely low pour point
- good elastomer compatibility to prevent leaks



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	876,0	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm ² /s	14,2	DIN 51562-10
Viscosity at 40°C	mm ² /s	76,3	DIN 51562-10
Viscosity index VI		194	DIN ISO 2909
Brookfield Viscosity	mPa*s	45.000	ASTM D 2983
Pourpoint	°C	-42	DIN ISO 3016
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. October 2019