



RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C



ART.-NR. 1410116

1,5 L | 1410116-150
5 L | 1410116-005
10 L | 1410116-010
20 L | 1410116-020

RECOMMENDATIONS ASTM D6210 TYP III-FF, ASTM D3306, ASTM D4985 | CATEPILLAR EC-1, CUMMINS CES 14603, CUMMINS SB 3666132 | DETROIT DIESEL CORPORATION 7SE298, TMC RP329 TYPE A | VERLÄNGERTE LEBENSDAUER DURCH SCA - SUPPLEMENT COOLANT ADDITIVES

RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C is a ready to use, prediluted with water ethylene glycol coolant, based on low silicate technology in combination with nitrite and molybdate. **RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C** is used as a cooling and heat transferring fluid in combustion engines and in particular for heavy duty applications.

RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C is suitable for gasoline, diesel, and natural gas powered automotive and industrial engines and is particularly recommended for heavy duty engines, where high temperature aluminium protection is important.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

Application Notes

RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C** to radiator to fill line.

Characteristics

RAVENOL HDT Heavy Duty Truck Cool. Premix -40°C offers:

- High-quality corrosion additives for optimal corrosion and aluminium protection
- Excellent pitting corrosion
- No scale formation by phosphate free inhibitor package
- No gel formation or drop-out
- engineered low-silicate inhibitor package for uniform and homogenous protective layer



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	1080	EN ISO 12185
Colour		grün	visual
pH-Value		8,0	ASTM D 1287
Freezing point	°C	-40	ASTM D 1177

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 13. November 2019