



RAVENOL MARINEOIL DIESEL SHPD 15W-40

RAVENOL MARINEOIL DIESEL SHPD 15W-40 is a SHPD engine oil for marine diesel engines.

RAVENOL MARINEOIL DIESEL SHPD 15W-40 is especially produced for extended oil change intervals (under consideration of the manufacturer instruction)

Specifications

API CF, API CI-4, ACEA E7, ACEA B4

Practice and tested in aggregates with filling

VETUS DEUTZ, Steyr, MTU, VOLVO, PENTA, Caterpillar, IVECO, MAN, Mercruiser, PERKINS, NANNI Diesel, YANMAR, Detroit Diesel, SULZER, SKL

Characteristic

RAVENOL MARINEOIL DIESEL SHPD 15W-40 offers :

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Characteristics	Unit	Data	Audit
Colour		blau	visual
Density at 20°C	kg/m ³	885	EN ISO 12185
Viscosity at 40°C	mm ² /s	106,0	DIN 51 562
Viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity index VI		144	DIN ISO 2909
Flash point (COC)	°C	222	DIN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016
TBN	mg KOH/g	11,5	DIN ISO 3771
Sulphated ash	%wt.	1,3	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

13.01.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41