



## RAVENOL MARINEOIL PETROL 20W-50

RAVENOL MARINEOIL PETROL 20W-50 is a multi-range engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

### Specifications

API SL

### Practice and tested in aggregates with filling

YANMAR, Mercruiser, VOLVO Penta AB, Kohler

### Characteristic

RAVENOL MARINEOIL PETROL 20W-50 offers:

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

Characteristics	Unit	Data	Audit
Colour		blau	visual
Density at 20°C	kg/m <sup>3</sup>	886	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	150,0	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	18,0	DIN 51 562
Viscosity index VI		133	DIN ISO 2909
Flash point (COC)	°C	228	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016
TBN	mg KOH/g	8,5	DIN ISO 3771
Sulphated ash	%wt.	1,3	DIN 51757

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

13.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41