



## RAVENOL SCR 32 Screw Kompressorenöl

RAVENOL SCR 32 Screw Kompressorenöl is optimal alloyed mineral screw compressor oil, with a high performance level and a wide application area of the whole industry. It is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

### Application Notes

RAVENOL SCR 32 Screw Kompressorenöl is used in compressors.

### Quality Classifications

RAVENOL SCR 32 Screw Kompressorenöl is tried and tested for aggregates specifying:

### Specifications

Kennzeichnung nach DIN 51 502: HLP DIN 51 524, Teil 2, FZG-Test A 8,3/90: Die 12. Laststufe wird sicher erreicht

### Characteristic

RAVENOL SCR 32 Screw Kompressorenöl offers:

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Characteristics	Unit	Data	Audit
Colour		yellow brown	visual
Density at 20°C	kg/m <sup>3</sup>	872	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	32,7	DIN 51 562
Viscosity index VI		98	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016
FZG-Test A/8,3/90 damage loading step		12	DIN 51 354
Aging stability, TOST	st	2000	DIN 51 587

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

05.04.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41