



RAVENOL SSV SAE 0W-30



ART.-NR. 1111145

1 L | 1111145-001
4 L | 1111145-004
20 L | 1111145-020
20 L | 1111145-B20
1000 L | 1111145-700

VISCOSITY 0W-30

SPECIFICATIONS API SL | ACEA A5 | ACEA B5

APPROVALS VOLVO VCC 95200377 (SERVICE FILL) | MB-FREIGABE 229.6

RECOMMENDATIONS MB 229.6

RAVENOL SSV Fuel Economy SAE 0W-30 is a PAO (Polyalphaolefin) based, fully synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

RAVENOL SSV Fuel Economy SAE 0W-30 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

With its new formulation, **RAVENOL SSV Fuel Economy SAE 0W-30** provides a safe layer of lubrication even at very high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL SSV Fuel Economy SAE 0W-30** helps to protect the environment by reducing emissions.

Extended oil change intervals according to the manufacturer's instructions.

Application Notes

RAVENOL SSV FUEL ECONOMY SAE 0W-30 is universal, fuel-efficient engine oil. It is a premium product for gasoline and diesel engine passenger cars. Suitable for all petrol and diesel passenger cars with and without turbo charger, especially recommended for full synthetic all-season motor oils.

Characteristics

RAVENOL SSV FUEL ECONOMY SAE 0W-30 offers:

- universal application in all modern petrol and diesel engines
- quick lubrication of the engine even at temperatures below -30 °C
- low evaporation tendency, therefore a lower oil consumption
- safety against accumulation of sludge, coking and corrosion even under unfavourable operating conditions
- guarantee of the function of the hydro tappets at all temperatures
- no oil limited deposits in combustion chambers, at the piston ring and valves
- unchanged viscosity during the whole oil change interval, high viscosity index



- neutral against sealing materials
- Miscibility with all commercially available engine oils. Flushing is not required.

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	838,0	EN ISO 12185
Colour		brown	visual
Viscosity at 100°C	mm ² /s	9,7	DIN 51 562
Viscosity at 40°C	mm ² /s	52,9	DIN 51 562
Viscosity index VI		172	DIN ISO 2909
HTHS at 150°C	mP?*s	2,97	ASTM D5481
CCS Viscosity at -35°C	mPa*s	4610	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -40°C	mPa*s	16.300	ASTM D4684
Pourpoint	°C	-57	DIN ISO 3016
Noack Volatility	% M/M	8,1	ASTM D5800/b
Flash point	°C	234	DIN ISO 2592
TBN	mg KOH/g	9,7	ASTM D2896
Sulphated ash	%wt.	1,2	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 15. October 2019