



RAVENOL STOU SAE 10W-40

RAVENOL STOU SAE 10W-40 is an up-to-date multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-40 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons.

Application Notes

RAVENOL STOU SAE 10W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Quality Classifications

Specifications

API GL-4, API CG-4, SAE 10w-40, ACEA E2, SAE 80W, SAE 80w-90, 85W-90, 85W, 80W, HLP-D/HVLP-D (ISO VG 32-100)

Practice and tested in aggregates with filling

Massey-Ferguson M 1127, Massey-Ferguson M 1139, Massey-Ferguson M 1144, MB-Blatt 227.1, John Deere J 27 A, J20 C/D, Steyr 38788001, Case International J I Case MS 1118/1209/1206, FIAT AF 87, Ford ESN-M2C-41B,-86A, -121E, -134D, -159 B/C, Ford NH 024C, Ford NH 324B, Ford NH 540B, International Harvester B6, MIL-L-2105, MIL-L-2104 D, Allison C-4, Caterpillar TO-2, ZF TE-ML 06B, ZF TE-ML 07B, Denison HF 2, Holman Compair/Atlas Copco Kompressor

Characteristic

RAVENOL STOU SAE 10W-40 offers:

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- A high and stable viscosity index
- An excellent extreme pressure properties

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Colour | | gelbbraun | visual |
| Density at 15°C | kg/m ³ | 874 | EN ISO 12185 |
| Viscosity at -25°C | mPa.s | 5000 | ASTM D5293 |
| Viscosity at 40°C | mm ² /s | 88,4 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 13,6 | DIN 51 562 |
| Viscosity index VI | | 156 | DIN ISO 2909 |
| Flash point (COC) | °C | 220 | DIN ISO 2592 |
| Pourpoint | °C | -40 | DIN ISO 3016 |
| TBN | mg KOH/g | 10,9 | DIN ISO 3771 |
| Sulphated ash | %wt. | 1,45 | DIN 51 575 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41