



RAVENOL STOU SAE 15W-40

RAVENOL STOU SAE 15W-40 is a multi-purpose super universal tractor oil for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers as listed below, and can be used in engines, transmissions and hydraulic systems of most equipment in all seasons which require this grade of oil.

Application Notes

RAVENOL STOU SAE 15W-40 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes and PTO transmissions) and as a hydraulic oil where this specification of product is required. Can also be used as compressor oil.

Specifications

API SF/CE/CF-4/GL-4, ACEA E1, CCMC G2/D4

Practice and tested in aggregates with filling

ZF TE-ML 06B, ZF TE-ML 07B, Allison C-4, Caterpillar TO-2, Ford M2C-159C, Ford M2C-86A, Ford M2C-134D, MF M-1143/1144, MB 227.1, John Deere J 27, NH 420A, NH 410B

Characteristic

RAVENOL STOU SAE 15W-40 offers:

- Excellent viscosity-temperature behaviour
- Exceptional cold starting abilities
- Excellent detergent and dispersant properties
- High resistance to ageing

| Characteristics | Unit | Data | Audit |
|--------------------|--------------------|--------------|--------------|
| Colour | | yellow brown | visual |
| Density at 20°C | kg/m ³ | 885 | EN ISO 12185 |
| Viscosity at 40°C | mm ² /s | 93,5 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 13,0 | DIN 51 562 |
| Viscosity index VI | | 137 | DIN ISO 2909 |
| Flash point (COC) | °C | 218 | DIN ISO 2592 |
| Pourpoint | °C | -27 | DIN ISO 3016 |
| TBN | mg KOH/g | 11,3 | DIN ISO 3771 |
| Sulphated ash | %wt. | 1,55 | DIN 51 575 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41